

SSH-78-4



SnapStak® Hanger for 7/8 in coaxial cable, quadruple stack capability, includes reinforcement bar

Product Classification

| | |
|----------------------|------------------------------|
| Product Type | Hanger kit |
| Product Brand | SnapStak® |
| Ordering Note | ANDREW® non-standard product |

General Specifications

| | |
|--------------------------|-----------------------------|
| Cables per Hanger | 1 |
| Color | Silver |
| Hanger Type | Snap-in hanger |
| Mounting | 3/4 in drilled cable ladder |

Dimensions

| | |
|--|--------------------|
| Maximum Stack Height | 4 |
| Height | 40.9 mm 1.61 in |
| Width | 40.1 mm 1.579 in |
| Length | 64 mm 2.52 in |
| Compatible Cable Diameter Range | 26.7–31 mm |
| Compatible Diameter, maximum | 31 mm 1.22 in |
| Compatible Diameter, minimum | 26.7 mm 1.051 in |
| Nominal Size | 7/8 in |

Electrical Specifications

| | |
|------------------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum | 0.1 dB |

Material Specifications

| | |
|----------------------|-----------------|
| Material Type | Stainless steel |
|----------------------|-----------------|

SSH-78-4

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F)

Corrosion Resistance, minimum with no degradation ≥500 hours in salt spray chamber

Environmental Strength Capability Double cable weight

Packaging and Weights

Height, packed 15.6 cm | 6.142 in

Width, packed 14.8 cm | 5.827 in

Length, packed 10.8 cm | 4.252 in

Packaging quantity 10

Weight, gross 0.42 kg | 0.926 lb

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.andrew.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |

Included Products

SSHR-10 – SnapStak Hanger Reinforcement Bar, PIM free bar provides the ability to add an additional cable run to the stack

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

SSHR-10



SnapStak Hanger Reinforcement Bar, PIM free bar provides the ability to add an additional cable run to the stack

Product Classification

| | |
|----------------------|--|
| Product Type | Adapter |
| Product Brand | SnapStak® |
| Ordering Note | ANDREW® standard product in the United States and Canada |

General Specifications

| | |
|--------------------|---------------------|
| Accessories | Adapters |
| Color | Black |
| Mounting | 3/4 in through hole |

Dimensions

| | |
|---------------|-------------------|
| Height | 76.2 mm 3 in |
| Width | 25.4 mm 1 in |
| Length | 6.35 mm 0.25 in |

Material Specifications

| | |
|----------------------|--------------------|
| Material Type | Engineered plastic |
|----------------------|--------------------|

Mechanical Specifications

| | |
|---------------------------|---|
| Maximum Loading | Quadruple stack for SSH-M Triple stack for hangers SSH-XL, SSH-L Triple stack, 1-5/8 in cable |
| Vibration Survival | ≥4 hours at resonant frequency |

Environmental Specifications

| | |
|---|---|
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| UV Resistance, minimum with no degradation | ≥1000 hours exposure in accelerated UV life chamber |

Packaging and Weights

| | |
|-----------------------|------------------|
| Height, packed | 17 cm 6.693 in |
|-----------------------|------------------|

SSHR-10

| | |
|---------------------------|--------------------|
| Width, packed | 13 cm 5.118 in |
| Length, packed | 10 cm 3.937 in |
| Packaging quantity | 10 |
| Weight, gross | 0.15 kg 0.331 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Below maximum concentration value |
| REACH-SVHC | Compliant as per SVHC revision on www.andrew.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |

