

FT-36VAAHIN



HELIAX® 36 MULTIMODE FIBER TRUNK Cca ARMORED

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Product Type

Wireless Fiber Cable Assemblies

Product Series

FT

Ordering Note

ANDREW® non-standard product

General Specifications

Color, connector A

Aqua

Color, connector B

Aqua

Construction Type

Discrete fiber trunk

Interface, Connector A

LC/UPC

Interface Feature, connector A

Uniboot

Interface Body Style, connector A

Straight

Interface, Connector B

LC/UPC

Interface Feature, connector B

Uniboot

Interface Body Style, connector B

Straight

Jacket Color

Black

Total Fibers, quantity

36

Dimensions

Cable Assembly Length Range (m)

1 – 300

Diameter Over Jacket

9.6 mm | 0.378 in

Material Specifications

Jacket Material

Low Smoke Zero Halogen (LSZH)

Mechanical Specifications

FT-36VAAHIN

Minimum Bend Radius 20 mm | 0.787 in

Optical Specifications

Fiber Mode Multimode

Fiber Type OM4

Insertion Loss, typical note Insertion loss is measured at 1310 and 1550 nm

Insertion Loss, typical 0.5

Environmental Specifications

Operating Temperature -40 °C to +75 °C (-40 °F to +167 °F)

EN50575 CPR Cable EuroClass Fire Performance Cca

EN50575 CPR Cable EuroClass Smoke Rating s1

EN50575 CPR Cable EuroClass Droplets Rating d1

EN50575 CPR Cable EuroClass Acidity Rating a1

Environmental Space Indoor | Outdoor

Packaging and Weights

Cable weight 134 kg/km | 90.044 lb/kft

* Footnotes

Insertion Loss, typical note Insertion loss is measured at a room temp of +20°C (+68°F)