

TA-NMHM

N Male to 4.3-10 Male Low-PIM Adapter

Product Classification

Product Type Adapter

General Specifications

Body Style Straight
Inner Contact Plating Silver
Interface N Male
Interface 2 4.3-10 Male
Mounting Angle Straight
Outer Contact Plating Trimetal

Dimensions

Length 46.15 mm | 1.817 in
Diameter 24 mm | 0.945 in

Electrical Specifications

3rd Order IMD at Frequency -120 dBm @ 1800 MHz
3rd Order IMD Test Method Two +43 dBm carriers
Connector Impedance 50 ohm
dc Test Voltage 2500 V
Inner Contact Resistance, maximum 1 mOhm
Insulation Resistance, minimum 5000 MOhm
Operating Frequency Band 0 – 6000 MHz
Outer Contact Resistance, maximum 1 mOhm

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
0–4000 MHz	1.052	32
4000–6000 MHz	1.106	26

Mechanical Specifications

Coupling Nut Proof Torque 8 N-m | 70.806 in lb

TA-NMHM

Coupling Nut Retention Force	450 N 101.164 lbf
Interface Durability	100 cycles
Mechanical Shock Test Method	IEC 60068-2-27

Environmental Specifications

Operating Temperature	-55 °C to +85 °C (-67 °F to +185 °F)
Storage Temperature	-65 °C to +125 °C (-85 °F to +257 °F)
Attenuation, Ambient Temperature	20 °C 68 °F
Average Power, Ambient Temperature	40 °C 104 °F
Average Power, Inner Conductor Temperature	100 °C 212 °F
Climatic Sequence Test Method	IEC 60068-1
Corrosion Test Method	IEC 60068-2-11
Damp Heat Steady State Test Method	IEC 60068-2-3
Immersion Depth	1 m
Immersion Test Mating	Mated
Immersion Test Method	IEC 60529:2001, IP68
Thermal Shock Test Method	IEC 60068-2-14
Vibration Test Method	IEC 60068-2-6

Packaging and Weights

Weight, net	67.6 g 0.149 lb
--------------------	-------------------

* Footnotes

Immersion Depth	Immersion at specified depth for 24 hours
------------------------	-------------------------------------------