

# FT-36PAAHIN



HELIAX® Modular Fiber Cable, assembly, 36 multi mode fibers, End 1: DLC GEN1.5; End 2: DLC GEN 1.5; CPR Cca cable. Anti-rodent with E-Glass Protection.

## Product Classification

### Regional Availability

Asia | Australia/New Zealand | China | EMEA | Europe | India | Latin America | North America

### Product Type

Wireless Fiber Cable Assemblies

### Product Series

FT

### Ordering Note

ANDREW® non-standard product

## General Specifications

### Color, connector A

Aqua

### Color, connector B

Aqua

### Construction Type

Discrete fiber trunk

### Interface, Connector A

LC/UPC

### Interface Feature, connector A

Uniboot

### Interface Body Style, connector A

Straight

### Interface, Connector B

LC/UPC

### Interface Feature, connector B

Uniboot

### Interface Body Style, connector B

Straight

### Jacket Color

Black

### Total Fibers, quantity

36

## Dimensions

### Cable Assembly Length Range (m)

1 – 300

### Diameter Over Jacket

8.9 mm | 0.35 in

## Material Specifications

### Jacket Material

Low Smoke Zero Halogen (LSZH)

## Mechanical Specifications

# FT-36PAAHIN

---

**Minimum Bend Radius** 20 mm | 0.787 in

## Optical Specifications

**Fiber Mode** Multimode

**Fiber Type** OM4, bend insensitive

**Insertion Loss, typical note** Insertion loss is measured at 1310 and 1550 nm

**Insertion Loss, typical** 0.5

## Environmental Specifications

**Operating Temperature** -40 °C to +75 °C (-40 °F to +167 °F)

**EN50575 CPR Cable EuroClass Fire Performance** Cca

**EN50575 CPR Cable EuroClass Smoke Rating** s1

**EN50575 CPR Cable EuroClass Droplets Rating** d1

**EN50575 CPR Cable EuroClass Acidity Rating** a1

**Environmental Space** Indoor | Outdoor

## Packaging and Weights

**Cable weight** 78 kg/km | 52.414 lb/kft

## \* Footnotes

**Insertion Loss, typical note** Insertion loss is measured at a room temp of +20°C (+68°F)