

# FT-24VAAHIN

---



HELIAX® 24 MULTIMODE FIBER TRUNK Cca ARMORED.

## Product Classification

### Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

### Product Type

Wireless Fiber Cable Assemblies

### Product Series

FT

### Ordering Note

ANDREW® non-standard product

## General Specifications

### Color, connector A

Aqua

### Color, connector B

Aqua

### Construction Type

Discrete fiber trunk

### Interface, Connector A

LC/UPC

### Interface Feature, connector A

Uniboot

### Interface Body Style, connector A

Straight

### Interface, Connector B

LC/UPC

### Interface Feature, connector B

Uniboot

### Interface Body Style, connector B

Straight

### Jacket Color

Black

### Total Fibers, quantity

24

## Dimensions

### Cable Assembly Length Range (m)

1 – 300

### Diameter Over Jacket

9.2 mm | 0.362 in

## Mechanical Specifications

### Minimum Bend Radius

20 mm | 0.787 in

## Optical Specifications

# FT-24VAAHIN

---

<b>Fiber Mode</b>	Multimode
<b>Fiber Type</b>	OM4, bend insensitive
<b>Insertion Loss, typical note</b>	Insertion loss is measured at 1310 and 1550 nm
<b>Insertion Loss, typical</b>	0.5

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +75 °C (-40 °F to +167 °F)
<b>EN50575 CPR Cable EuroClass Fire Performance</b>	Cca
<b>EN50575 CPR Cable EuroClass Smoke Rating</b>	s1
<b>EN50575 CPR Cable EuroClass Droplets Rating</b>	d1
<b>EN50575 CPR Cable EuroClass Acidity Rating</b>	a1
<b>Environmental Space</b>	Indoor   Outdoor

## Packaging and Weights

<b>Cable weight</b>	131 kg/km   88.028 lb/kft
---------------------	---------------------------

## \* Footnotes

**Insertion Loss, typical note** Insertion loss is measured at a room temp of +20°C (+68°F)