

# LLPX310R-V1



4-port sector antenna, 4x 2300–2700 MHz, 65° HPBW, 2x RET with manual override

- Integrated Internal Remote Electrical Tilt (RET), with independent control of electrical tilt with manual override on all arrays

## General Specifications

<b>Antenna Type</b>	Sector
<b>Band</b>	Single band
<b>Grounding Type</b>	RF connector inner conductor and body grounded to reflector and mounting bracket
<b>Performance Note</b>	Outdoor usage   Wind loading figures are validated by wind tunnel measurements described in white paper WP-112534-EN
<b>Radome Material</b>	Polyester fiberglass pultrusion
<b>RF Connector Interface</b>	7-16 DIN Female
<b>RF Connector Location</b>	Bottom
<b>RF Connector Quantity, high band</b>	4
<b>RF Connector Quantity, mid band</b>	0
<b>RF Connector Quantity, low band</b>	0
<b>RF Connector Quantity, total</b>	4

## Remote Electrical Tilt (RET) Information

<b>RET Interface</b>	8-pin DIN Male
<b>RET Interface, quantity</b>	1 male
<b>Input Voltage</b>	10–30 Vdc
<b>Internal RET</b>	High band (2)
<b>Power Consumption, idle state, maximum</b>	2 W
<b>Power Consumption, normal conditions, maximum</b>	13 W
<b>Protocol</b>	3GPP/AISG 2.0 (Single RET)

## Dimensions

<b>Width</b>	300 mm   11.811 in
<b>Depth</b>	115 mm   4.528 in

# LLPX310R-V1

**Length** 1077 mm | 42.402 in  
**Net Weight, without mounting kit** 13 kg | 28.66 lb

## Port Configuration



## Electrical Specifications

**Impedance** 50 ohm  
**Operating Frequency Band** 2300 – 2700 MHz  
**Polarization**  $\pm 45^\circ$

## Electrical Specifications

Frequency Band, MHz	2300–2500	2500–2700
Gain, dBi	17.2	17.8
Beamwidth, Horizontal, degrees	65	63
Beamwidth, Vertical, degrees	7	6.5
Beam Tilt, degrees	0–10	0–10
USLS (First Lobe), dB	18	18
Front-to-Back Ratio at 180°, dB	30	30
Isolation, Cross Polarization, dB	30	30
VSWR   Return loss, dB	1.43   15.0	1.43   15.0

# LLPX310R-V1

---

<b>PIM, 3rd Order, 2 x 20 W, dBc</b>	-150	-150
<b>Input Power per Port, maximum, watts</b>	250	250

## Mechanical Specifications

<b>Wind Loading @ Velocity, maximum</b>	450.0 N @ 160 km/h (101.2 lbf @ 160 km/h)
<b>Wind Speed, maximum</b>	200 km/h (124 mph)

## Packaging and Weights

<b>Width, packed</b>	366 mm   14.409 in
<b>Depth, packed</b>	213 mm   8.386 in
<b>Length, packed</b>	1260 mm   49.606 in
<b>Weight, gross</b>	21.5 kg   47.399 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant
UK-ROHS	Compliant




## Included Products

T-045-GL-E	-	Adjustable Tilt Pipe Mounting Kit for 2.0"-4.5" (60-115mm) OD round members for panel antennas. Includes 2 clamp sets.
------------	---	--

## \* Footnotes

<b>Performance Note</b>	Severe environmental conditions may degrade optimum performance
-------------------------	---

# T-045-GL-E



Adjustable Tilt Pipe Mounting Kit for 2.0"-4.5" (60-115mm) OD round members for panel antennas. Includes 2 clamp sets.

## Product Classification

**Product Type** Adjustable tilt mounting kit

## General Specifications

**Application** Outdoor

**Color** Silver

## Dimensions

**Compatible Length, maximum** 1200 mm | 47.244 in

**Compatible Length, minimum** 850 mm | 33.465 in

**Compatible Diameter, maximum** 115 mm | 4.528 in

**Compatible Diameter, minimum** 60 mm | 2.362 in

**Antenna-to-Pipe Distance** 85 mm | 3.346 in

**Bracket-to-Bracket Distance** 761 mm | 29.961 in

**Weight, net** 6 kg | 13.228 lb

## Material Specifications

**Material Type** Galvanized steel

## Mechanical Specifications

**Mechanical Tilt** 0°-10°

## Packaging and Weights

**Included** Brackets | Hardware

**Packaging quantity** 1

## Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value

# T-045-GL-E

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

