

# S4-90M-R1-V2



## 8-port Planar Array Antenna, 3300–3800 MHz, 90° HPBW, 1x RET

- Planar array antenna – 4 columns
- Single internal RET control for all four antenna arrays
- Designed for beamforming, includes calibration port
- Optimized for software defined split six sector applications
- Fits in the ANDREW AEKT solution

## General Specifications

<b>Antenna Type</b>	Sector
<b>Band</b>	Single band
<b>Calibration Connector Interface</b>	4.3-10 Female
<b>Calibration Connector Quantity</b>	1
<b>Color</b>	Light Gray (RAL 7035)
<b>Grounding Type</b>	RF connector inner conductor and body grounded to reflector and mounting bracket
<b>Performance Note</b>	Outdoor usage
<b>Radome Material</b>	PVC
<b>Radiator Material</b>	Low loss circuit board
<b>RF Connector Interface</b>	4.3-10 Female
<b>RF Connector Location</b>	Bottom
<b>RF Connector Quantity, high band</b>	8
<b>RF Connector Quantity, mid band</b>	0
<b>RF Connector Quantity, low band</b>	0
<b>RF Connector Quantity, total</b>	8

## Remote Electrical Tilt (RET) Information

<b>RET Hardware</b>	CommRET v1
<b>RET Interface</b>	8-pin DIN Female   8-pin DIN Male
<b>RET Interface, quantity</b>	1 female   1 male
<b>Internal RET</b>	High band (1)
<b>Power Consumption, idle state, maximum</b>	1 W
<b>Power Consumption, normal conditions, maximum</b>	8 W

# S4-90M-R1-V2

**Protocol** 3GPP/AISG 2.0 (Single RET)

## Dimensions

**Width** 307 mm | 12.087 in


**Depth** 118 mm | 4.646 in

**Length** 850 mm | 33.465 in

**Net Weight, without mounting kit** 8.64 kg | 19.048 lb

**TDD Column Spacing** 42 mm | 1.654 in

## Array Layout



Array	Freq (MHz)	Conns	RET (SRET)	AISG RET UID
<b>P1</b>	3300-3800	1-8	1	CPxxxxxxxxxxxxxxP1

(Sizes of colored boxes are not true depictions of array sizes)

## Port Configuration

# S4-90M-R1-V2



## Electrical Specifications

<b>Impedance</b>	50 ohm
<b>Operating Frequency Band</b>	3300 – 3800 MHz
<b>Polarization</b>	±45°
<b>Total Input Power, maximum</b>	400 W @ 50 °C

## Electrical Specifications

Frequency Band, MHz	3300–3600	3600–3800
Gain, dBi	15.5	16
Beamwidth, Horizontal, degrees	96	86
Beamwidth, Vertical, degrees	6.7	6.3
Beam Tilt, degrees	2–12	2–12
Beam Tilt Tolerance, degrees	±0.5	±0.5
USLS (First Lobe), dB	20	19
Front-to-Back Ratio at 180°, dB	29	29
Coupling level, Amp, Antenna port to Cal port, dB	26	26
Coupling level, max Amp Δ, Antenna port to Cal port, dB	±2	±2
Coupler, max Amp Δ, Antenna port to Cal port, dB	0.9	0.9
Coupler, max Phase Δ, Antenna port to Cal port, degrees	7	7
Isolation, Inter-band, dB	19	19
Isolation, Cross Polarization, port to port, dB	25	25

# S4-90M-R1-V2

VSWR   Return loss, dB	1.5   14.0	1.5   14.0
PIM, 3rd Order, 2 x 20 W, dBc	-140	-140
Input Power per Port at 50°C, maximum, watts	50	50

## Electrical Specifications, Broadcast 65°

Frequency Band, MHz	<b>3300–3600</b>	<b>3600–3800</b>
Gain, dBi	16.4	16.4
Beamwidth, Horizontal, degrees	66	65
Beamwidth, Horizontal Tolerance, degrees	±4.0	±4.0
Beamwidth, Vertical, degrees	6.7	6.4
Beamwidth, Vertical Tolerance, degrees	±0.3	±0.3
USLS (First Lobe), dB	20	19

## Electrical Specifications, Service Beam

Frequency Band, MHz	<b>3300–3600</b>	<b>3600–3800</b>
Steered 0° Gain, dBi	20.7	21.1
Steered 0° Gain Tolerance, dBi	±0.6	±0.3
Steered 0° Beamwidth, Horizontal, degrees	25	24
Steered 0° CPR at Beampeak, dB	19	16
Steered 0° Horizontal Sidelobe, dB	12	12
Steered 13° USLS (First Lobe), dB	6	3
Steered 30° Gain, dBi	19.9	20.1
Steered 30° Gain Tolerance, dBi	±0.5	±0.5
Steered 30° Beamwidth, Horizontal, degrees	28	26
Steered 30° CPR at Beampeak, dB	19	17
Steered 30° CPR over 10 dB Beamwidth, dB	14	14
Steered 30° Horizontal Sidelobe, dB	9	9
Steered 42° Front-to-Back Total Power at 180° ± 30°, dB	5	5

## Electrical Specifications, Soft Split

Frequency Band, MHz	<b>3300–3600</b>	<b>3600–3800</b>
Gain, dBi	19.8	20.2
Beamwidth, Horizontal, degrees	31	29
CPR at Beampeak, dB	18	16
Horizontal Sidelobe, dB	18	18

## Mechanical Specifications

# S4-90M-R1-V2

---

<b>Mechanical Tilt Range</b>	0°–24°
<b>Wind Loading @ Velocity, frontal</b>	284.0 N @ 150 km/h (63.8 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, lateral</b>	56.0 N @ 150 km/h (12.6 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, maximum</b>	286.0 N @ 150 km/h (64.3 lbf @ 150 km/h)
<b>Wind Loading @ Velocity, rear</b>	343.0 N @ 150 km/h (77.1 lbf @ 150 km/h)
<b>Wind Speed, maximum</b>	241 km/h (150 mph)

## Packaging and Weights

<b>Width, packed</b>	413 mm   16.26 in
<b>Depth, packed</b>	257 mm   10.118 in
<b>Length, packed</b>	1035 mm   40.748 in
<b>Weight, gross</b>	19.1 kg   42.108 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted



## Included Products

BSAMNT-3	–	Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.
----------	---	--

## \* Footnotes

<b>Performance Note</b>	Severe environmental conditions may degrade optimum performance
-------------------------	---

# BSAMNT-3



Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.

## Product Classification

**Product Type** Downtilt mounting kit

## General Specifications

**Application** Outdoor

**Color** Silver

## Dimensions

**Compatible Diameter, maximum** 115 mm | 4.528 in

**Compatible Diameter, minimum** 60 mm | 2.362 in

**Weight, net** 6.2 kg | 13.669 lb

## Material Specifications

**Material Type** Galvanized steel

## Packaging and Weights

**Included** Brackets | Hardware

**Packaging quantity** 1

**Weight, gross** 6.4 kg | 14.11 lb

## Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.andrew.com/ProductCompliance">www.andrew.com/ProductCompliance</a>
ROHS	Compliant
UK-ROHS	Compliant

# BSAMNT-3

---

