

VVPX310R-V5



4-port sector antenna, 4x 1710–2690 MHz, 65° HPBW, 2x RET with manual override

- Integrated Internal Remote Electrical Tilt (RET), with independent control of electrical tilt with manual override on all arrays

Alternative products available:

VV-65A-R1B

4-port sector antenna, 4x 1695–2690 MHz, 65° HPBW, 1x RET and 1x SBT, the two highband arrays utilize a common tilt.

General Specifications

Antenna Type	Sector
Band	Single band
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage
Radome Material	ASA, UV stabilized
RF Connector Interface	7-16 DIN Female
RF Connector Location	Bottom
RF Connector Quantity, high band	4
RF Connector Quantity, mid band	0
RF Connector Quantity, low band	0
RF Connector Quantity, total	4

Remote Electrical Tilt (RET) Information

RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 1 male
Input Voltage	10–30 Vdc
Internal RET	High band (2)
Power Consumption, idle state, maximum	2 W
Power Consumption, normal conditions, maximum	13 W
Protocol	3GPP/AISG 2.0 (Single RET)

VVPX310R-V5

Dimensions

Width	290 mm 11.417 in
Depth	103 mm 4.055 in
Length	1328 mm 52.283 in
Net Weight, without mounting kit	12.5 kg 27.558 lb

Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1710 – 2690 MHz
Polarization	±45°

Electrical Specifications

Frequency Band, MHz	1710–1920	1920–2180	2300–2690
Gain, dBi	17	17.7	18.4
Beamwidth, Horizontal, degrees	68	66.8	63
Beamwidth, Vertical, degrees	8.1	7.2	5.9
Beam Tilt, degrees	0–10	0–10	0–10
USLS (First Lobe), dB	19	19	18
Front-to-Back Ratio at 180°, dB	29	30	33
CPR at Boresight, dB	18	18	18
CPR at Sector, dB	13	10	9
Isolation, Cross Polarization, dB	30	30	30
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150
Input Power per Port, maximum, watts	250	250	250

Mechanical Specifications

Wind Loading @ Velocity, maximum	560.0 N @ 160 km/h (125.9 lbf @ 160 km/h)
Wind Speed, maximum	200 km/h (124 mph)

Packaging and Weights

Width, packed	360 mm 14.173 in
Depth, packed	216 mm 8.504 in
Length, packed	1510 mm 59.449 in

VVPX310R-V5

Regulatory Compliance/Certifications

Agency	Classification
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.andrew.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant



Included Products

- T-041-GL-E – Adjustable Tilt Pipe Mounting Kit for 2.0"-4.5" (60-115mm) OD round members for panel antennas. Includes 2 clamp sets.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance