## SA-3C



PIM-Guard® Three-Way Snap-in Stand-off Adapter has two slots for round member attachment and 3/8" holes for angle adapter integration. It includes three 3/4" holes for Snap-in hangers, supporting three 4-17mm or two 26-42mm cable stacks per hole

#### **Product Classification**

Product Type Stand-off mount
Product Brand PIM-Guard®

Ordering Note ANDREW® standard product (Global)

General Specifications

Adapter Type Stand-off adapter

**Color** Black

Mounting 3/4 in through hole | 3/8 in through hole | Round member

**Dimensions** 

Maximum Stack Height 3

 Height
 36.322 mm | 1.43 in

 Outside Width
 40.132 mm | 1.58 in

 Outside Length
 87.122 mm | 3.43 in

Material Specifications

Material Type Engineered polymer

Mechanical Specifications

**Maximum Loading**Triple stack for hangers SSH-411, SSH-1117

**Vibration Survival** ≥4 hours at resonant frequency

**Environmental Specifications** 

**Operating Temperature**  $-40 \,^{\circ}\text{C} \text{ to } +85 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +185 \,^{\circ}\text{F})$ 

Environmental Strength Capability Double cable weight

**UV Resistance, minimum with no degradation** ≥1000 hours



# SA-3C

## Packaging and Weights

 Height, packed
 17 cm | 6.693 in

 Width, packed
 13 cm | 5.118 in

 Length, packed
 10 cm | 3.937 in

Packaging quantity 10

**Weight, gross** 0.27 kg | 0.595 lb

## Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.andrew.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



#### \* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

