

L5CLAMP-CNL-3B



KwikClamp™ Hanger for 7/8 in coaxial cable, triple stack, C-Channel compatible; includes hardware

Product Classification

| | |
|----------------------|---|
| Product Type | Hanger kit |
| Product Brand | KwikClamp™ |
| Ordering Note | ANDREW® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box |

General Specifications

| | |
|--------------------------|----------------------------------|
| Cables per Hanger | 1 |
| Color | Black |
| Hanger Type | KwikClamp™ hanger |
| Mounting | Channel section 40 x 22 x 1.5 mm |

Dimensions

| | |
|-------------------------------------|-------------------|
| Maximum Stack Height | 3 |
| Height | 197 mm 7.756 in |
| Width | 45 mm 1.772 in |
| Length | 32 mm 1.26 in |
| Compatible Diameter, maximum | 28 mm 1.102 in |
| Compatible Diameter, minimum | 26 mm 1.024 in |
| Nominal Size | 7/8 in |
| Hanger Spacing, maximum | 1.83 m 6.004 ft |

Electrical Specifications

| | |
|------------------------------------|--------|
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum | 0.1 dB |

Material Specifications

| | |
|----------------------|--------------------------------------|
| Material Type | Engineered plastic Stainless steel |
|----------------------|--------------------------------------|

L5CLAMP-CNL-3B

Mechanical Specifications

Vibration Survival

≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature

-40 °C to +70 °C (-40 °F to +158 °F)

Corrosion Resistance, minimum with no degradation

≥500 hours in salt spray chamber

Environmental Strength Capability

Five times cable weight

UV Resistance, minimum with no degradation

≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed

33 cm | 12.992 in

Width, packed

22 cm | 8.661 in

Length, packed

27 cm | 10.63 in

Included

Hardware

Packaging quantity

100

Weight, gross

23 kg | 50.706 lb

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power