## UHA-3C



PIM-Guard®, Universal Three-Way Stand-off Adapter. Mounts snap-in hangers, grommets, and threaded rods onto towers with round members or 1/4" and 3/8" angle members, supporting three stacks for 4-17mm or two stacks for 26-40mm cables

- Attaches onto round and angle tower members with 1/2" banding
- Mounts polymer and metal snap-in hangers
- Mounts rubber grommets
- Includes insert to mount 3/8" threaded rod kits
- Provides three hanger mounting positions
- Optimized to reduce PIM while maximizing structural integrity

#### Product Classification

Product TypeStand-off mountProduct BrandPIM-Guard®

Ordering Note ANDREW® standard product (Global)

General Specifications

Adapter Type Stand-off adapter

**Color** Black

**Mounting** 3/4 in through hole | Tower angle members 1/4 | Tower angle members

3/8 | Tower round members 1" to 8" diameter

Dimensions

Maximum Stack Height 3

 Height
 43.688 mm | 1.72 in

 Outside Width
 50.292 mm | 1.98 in

 Outside Length
 76.2 mm | 3 in

Material Specifications

Material Type Engineered polymer

Mechanical Specifications

Maximum Loading Triple stack for hangers SSH-47, SSH-710, SSH-1014, SSH-411,

SSH-1117

**Vibration Survival** ≥4 hours at resonant frequency

ANDREW® an Amphenol company

# UHA-3C

#### **Environmental Specifications**

**Operating Temperature**  $-40 \,^{\circ}\text{C} \text{ to } +85 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +185 \,^{\circ}\text{F})$ 

**Environmental Strength Capability**Double cable weight

**UV Resistance, minimum with no degradation** ≥1000 hours

Packaging and Weights

 Height, packed
 17 cm | 6.693 in

 Width, packed
 13 cm | 5.118 in

 Length, packed
 10 cm | 3.937 in

Packaging quantity 10

**Weight, gross** 0.27 kg | 0.595 lb

### Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.andrew.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



#### \* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

