

CLT4NM-CO

Base Product



MQ Multiport cluster 4 ports cable assembly with interface type MQ female to N male, size 1/4"

Product Classification

| | |
|-----------------------|--------------------------------------|
| Product Type | Wireless transmission cable assembly |
| Product Series | MQ |
| Warranty | Two years |

General Specifications

| | |
|---|------------------|
| Attachment, Connector A | Factory attached |
| Attachment, Connector B | Factory attached |
| Body Style, Connector A | Straight |
| Body Style, Connector B | Straight |
| Interface, Connector A | MQ Female |
| Interface, Connector B | N Male |
| Specification Sheet Revision Level | A |

Dimensions

| | |
|---------------------|--------|
| Nominal Size | 1/4 in |
|---------------------|--------|

Port Configuration

| Pin Assignment | Label |
|----------------|-------------|
| 1 | MQ4-1 (R-) |
| 2 | MQ4-2 (CR-) |
| 3 | MQ4-3 (CL-) |
| 4 | MQ4-4 (L-) |

Mechanical Specifications

CLT4NM-CO

Minimum Bend Radius, multiple Bends 25.4 mm | 1 in

Minimum Bend Radius, single Bend 25.4 mm | 1 in

Environmental Specifications

Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F)

Immersion Test Method IEC 60529, IP67

* Footnotes

Warranty For more information, please consult our Product Warranty guidelines