

TW-4310-8NM



Torque Wrench for coupling torque of 4.3-10 connectors, 22 mm opening

OBSOLETE

Replaced By:

TW-4310-SP

Slim profile coupling torque wrench for 4.3-10 connectors, 22 mm opening, 8Nm torque

Product Classification

| | |
|----------------------|------------------------------|
| Product Type | Wrench |
| Product Brand | HELIAX® |
| Ordering Note | ANDREW® non-standard product |

General Specifications

| | |
|--------------------|---------------------------|
| Application | Torques 4.3-10 connectors |
| Calibration | 6 mo |
| Tool Type | Torque wrench |

Dimensions

| | |
|-----------------------|---------------------|
| Wrench Opening | 22.25 mm 0.876 in |
|-----------------------|---------------------|

Material Specifications

| | |
|----------------------|-------|
| Material Type | Steel |
|----------------------|-------|

Mechanical Specifications

| | |
|-------------------------|-----------------------|
| Torque Tolerance | ±0.8 N-m (±7.1 in lb) |
| Torque Value | 70.806 in lb 8 N-m |

Packaging and Weights

| | |
|-----------------------|-----------------------|
| Height, packed | 165.001 mm 6.496 in |
| Width, packed | 145.009 mm 5.709 in |

TW-4310-8NM

| | |
|---------------------------|------------------------|
| Length, packed | 330.022 mm 12.993 in |
| Carton Quantity | 10 |
| Packaging quantity | 1 |
| Weight, gross | 0.89 kg 1.962 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Below maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.andrew.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |

