


# CF141-XMPHMP-36IN



CF141 Jumper with interface types NEX10 Male push pull and 4.3-10 Male push pull , 36 in

## Product Classification

<b>Product Type</b>	Braided cable assembly
<b>Product Series</b>	CF141-50   RG402

## General Specifications

<b>Attachment, Connector A</b>	Factory attached
<b>Attachment, Connector B</b>	Factory attached
<b>Body Style, Connector A</b>	Straight
<b>Body Style, Connector B</b>	Straight
<b>Cable Family</b>	CF141-50   RG402
<b>Interface, Connector A</b>	NEX10 Male
<b>Interface, Connector B</b>	4.3-10 Male
<b>Specification Sheet Revision Level</b>	A

## Dimensions

<b>Length</b>	0.914 m   2.999 ft
<b>Diameter Over Jacket</b>	4.14 mm   0.163 in
<b>Nominal Size</b>	0.141 in

## Electrical Specifications

<b>3rd Order IMD at Frequency</b>	-117 dBm @ 1900 MHz
<b>3rd Order IMD Static</b>	-117 dBm
<b>3rd Order IMD Static Test Method</b>	Two +43 dBm carriers

## VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
100–3000 MHz	1.135	24

# C141-XMPHMP-36IN

## Jumper Assembly Sample Label



### Material Specifications

**Jacket Material** FEP

### Mechanical Specifications

**Minimum Bend Radius, multiple Bends** 40.132 mm | 1.58 in

**Minimum Bend Radius, single Bend** 10.16 mm | 0.4 in

### Environmental Specifications

**Immersion Test Method** Meets IEC 60529:2001, IP68 in mated condition