

# WPB-FIXM-HS

---



HELIAX® SureGuard® Boot for 1/4 in jumpers to antennas or devices

## Product Classification

<b>Product Type</b>	Weatherproofing boot
<b>Product Brand</b>	HELIAX®
<b>Ordering Note</b>	ANDREW® non-standard product

## General Specifications

<b>Application</b>	Provides additional moisture seal for cable connections
<b>Applications per Kit</b>	One 1/4 in to antenna or device connection
<b>Color</b>	Black

## Dimensions

<b>Width</b>	18 mm   0.709 in
<b>Length</b>	75 mm   2.953 in
<b>Cable Diameter for Seal, maximum</b>	7.75 mm   0.305 in
<b>Cable Diameter for Seal, minimum</b>	6.99 mm   0.275 in
<b>Inner Diameter</b>	4.5 mm   0.177 in
<b>Nominal Size</b>	1/4 in

## Material Specifications

<b>Material Type</b>	Silicone rubber
----------------------	-----------------

## Environmental Specifications

<b>Installation temperature</b>	-40 °C to +65 °C (-40 °F to +149 °F)
<b>Operating Temperature</b>	-40 °C to +85 °C (-40 °F to +185 °F)
<b>Storage Temperature</b>	-55 °C to +85 °C (-67 °F to +185 °F)
<b>UV Resistance Test Method</b>	ASTM G154-12a
<b>UV Resistance, minimum with no degradation</b>	≥1000 hours

# WPB-FIXM-HS

---

**Weather Resistance Test Method** IEC 60068-2-11 | IEC 60529:2001, IP68

## Packaging and Weights

<b>Height, packed</b>	30 mm   1.181 in
<b>Width, packed</b>	120 mm   4.724 in
<b>Length, packed</b>	140 mm   5.512 in
<b>Packaging quantity</b>	1
<b>Weight, gross</b>	25 g   0.055 lb