

# SSH-3642



PIM-Guard®, SnapTak® Adjustable Hanger, Gen 2. Fits 36.0 mm to 42.0 mm Cables – PIM Free Polymer Construction. No Grommets Required.

## Product Classification

Product Type	Hanger kit
Product Brand	PIM-Guard®   SnapTak®
Ordering Note	ANDREW® standard product (Global)

## General Specifications

Accessories	Hangers
Cables per Hanger	1
Color	Black
Hanger Type	Snap-in hanger
Mounting	3/4 in drilled cable ladder

## Dimensions

Maximum Stack Height	2
Maximum Stack Height, Coaxial	2
Height	81.32 mm   3.202 in
Width	42 mm   1.654 in
Length	114.21 mm   4.496 in
Compatible Cable Diameter Range	36–42 mm
Compatible Diameter, maximum	42 mm   1.654 in
Compatible Diameter, minimum	36 mm   1.417 in

## Electrical Specifications

Return Loss Effect, maximum	0.1 dB
DTF Effect, maximum	0.1 dB

## Material Specifications

Material Type	Engineered polymer
---------------	--------------------

# SSH-3642

---

## Mechanical Specifications

**Vibration Survival** ≥4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +85 °C (-40 °F to +185 °F)

**Environmental Strength Capability** Double cable weight

**UV Resistance, minimum with no degradation** ≥1000 hours exposure in accelerated UV life chamber

## Packaging and Weights

**Height, packed** 4.5 cm | 1.772 in

**Width, packed** 20 cm | 7.874 in

**Length, packed** 38 cm | 14.961 in

**Packaging quantity** 10

**Weight, gross** 0.36 kg | 0.794 lb

## \* Footnotes

**Maximum Stack Height** Fiber, Hybrid, Power